

1 2 3 4 5 6

REVISIONS

REV.	DESCRIPTION	DATE	REVISED BY
S0	CREATED DRAWING	03/02/21	Ruby_zhang

Electrical Character:  
 Rating voltage: 60V AC/DC  
 Insulation resistance: >100MΩ  
 Rating current: 1A  
 Contact resistance: ≤5mΩ

General Information:  
 Standard: IEC 61076-2-105  
 Connector Body: TPU  
 Contacts: Brass with Gold plating  
 Connector Locking System: Screw-locking  
 Ambient Temperature: -25°C~+85°C  
 Waterproof Rating: IP67/IP68  
 ALL MATERIALS ARE COMPLIANT WITH ROHS OR REACH

No.	Part No.	DESCRIPTION	Q'TY	UNIT
②	TK0060	Screw 9.2*6.5mm Brass with nickel plated	1	PC
①	DZ0047	M5 4pin male connector	1	PC

 Shenzhen Indus-connector Limited		TITLE: M5 4pin male solder connector			
		Customer Part No: --	REV. --	UNITS: mm	
DRAWN BY: Ruby_zhang CHECKED BY: David APPROVED BY: --	DATE: 03/02/21 DATE: 03/02/21 DATE: --	Indus-connector Part No: 5C003	REV. S0	SCALE: NONE	
Tolerances Unless Otherwise Specified: X. ±0.30 .X ±0.20 .XX ±0.10		PROJECTION:		SIZE: A4 SHEET: 1 OF 1	
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO INDUS-CONNECTOR INCORPORATED					

1 www.indus-connector.com 3 4 E-mail: info@indus-connector.com 6